



WARNING



Study, understand and follow all instructions provided with this product. Read these instructions carefully before installing, operating, servicing or repairing this tool. Keep these instructions in a safe accessible place.

INTENDED USE OF THE TOOL

The MCFL800 Collapsible Flood Light is designed to illuminate work areas by adjustment of the legs or use of the magnets. Do not use this tool outside of the designed intent. Never modify the tool for any other purpose or use.



WARNING



Caution: To help prevent personal injury

- Use of this product can expose you to chemicals including ethylene glycol, gasoline vapors and engine exhaust, which are known to the State of California to cause cancer, birth defects, or reproductive harm. For more information, visit www.P65Warnings.ca.gov. Always wear ANSI approved safety equipment, safety glasses and clothing when using this product. Study, understand, and follow all instructions provided with this product. Failure to read and follow all warnings and operating instructions may result in damages and serious injury or death.
- Always wear ANSI approved goggles when using this product. (Users and by standers).
- Never use this tool for any application other than for which it was designed.
- Only use accessories designed for this tool.
- Never alter or modify this tool in any way.
- Improper operation and/or maintenance of the tool, modification of the tool, or use of the tool with accessories not designed for it could result in serious injury or death.
- Always select the correct accessories of the correct size and design for the job that you are attempting to perform.
- Always work in a clean, safe, well-lit, organized and adequately equipped area.
- Do not begin repairs without assurance that vehicle is in secure position, and will not move during repair.



Made in China
to Matco specifications

DO NOT DISCARD – GIVE TO USER

1 YEAR LIMITED WARRANTY

The manufacturer warrants this product to the original user against defective material or workmanship for a period of 1 year from the date of purchase.

The manufacturer reserves the right to determine whether the part or parts failed because of defective material, workmanship or other causes. Failures caused by accident, alteration, or misuse are not covered by this warranty.

The manufacturer, at its discretion, will repair or replace product covered under this warranty free of charge. Repairs or replacements of products covered under this warranty are warranted for the remainder of the original warranty period.

The manufacturer or its authorized service representatives must perform all warranty repairs. Any repair to the product by unauthorized service representatives voids this warranty. The rights under this warranty are limited to the original user and may not be transferred to subsequent owners.

The warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. Some states do not allow the exclusion or limitations of incidental or consequential damages, so the above limitations may not apply to you.

BEFORE USE

When unpacking, check the parts diagram and part number listing on page 2 to make sure all parts are included. If any parts are missing or damaged, please call your distributor.

PRODUCT INFORMATION:

Adjustability. 360° rotating and folding head with adjustable and collapsible legs for getting light where you need it.

Power. 5,000mAh lithium battery for 6.5-7 hours at 800 lumens with quick charge USB adapter for faster recharging.

Mobility. Two 20 pound deployable magnets for mounting the floodlight where needed, and USB power-bank feature for charging your electronics from the light.

Specifications:

Light:	COB LED
Brightness:	800 lumens
Functions:	Both ON-One Side ON-Other Side ON-OFF
Battery:	5000mAH lithium battery (included) Wall charger output 5V 2A
Working time:	6.5-7 hours
Charing time:	3.5 hours
Product size:	5.3" x 7.9" x 2.4"
Weight:	1.1 lbs.

HOW TO RECHARGE

Connect the Micro-USB lead to the socket on the back of the flood light.

Connect the USB lead to the included quick charge wall adapter (other USB power sources will work, but may charge 2-3X slower).

The LED battery indicator will light up to indicate charging has started.

Once the unit is fully charged, ALL 3 indicator lights will light up.

Remove the adapter from the power source and disconnect from flood light.

CHARGING THE WORK LIGHT

1. Charge the battery prior to initial use.
2. The lights will change from Low-Medium-High during charging.
3. Charging time: ~3.5 hours
4. Battery type: Lithium-Ion 5,000mAh

NOTE

Best performance is achieved only after two or three complete charges.

Failure to recharge this flood light every three months may permanently damage or reduce performance.

PRODUCT DETAILS

