

Duo-Play Super Power Rechargeable Floodlight





4500 lumens of powerful multi-directional flooding output

CE RoHS IK07

Light Output

Twin heads deliver high quality, uniform illumination upto 4500 Lumens

Single button controlled multiple settings for optimized control over output and run-time

	MODE-1	MODE-2	MODE-3	MODE-4
				
LUMENS	750	1500	3000	4500
RUN TIME	12 hours	6 hours	3.5 hours	2 hours

STURDY CONSTRUCTION

IP54 Rated: Protected against dust and effects of water spray from any direction

IK07 Rated: Impact-proof nylon body and handle with sturdy polycarbonate lens will stand-up-to tough jobsite conditions

Versatile Use: Can be used as

1. Compact and portable, free standing floodlight bright enough to light up large areas.
2. On tripod stand to light overhead work and minimize shadows when directing the light downwards.

Operating Temperature: -10°C to +40°C (14°F to 104°F)

Replaceable battery gives infinite life to the worklight


Light has a working life upto 100,000 hours of use

Charging of Battery: 100-240V to 20V 1.1A charger (included)


Charge Time: 3.5 hours

SPECIFICATIONS


LIGHT	SMD – Floodlight
LUMEN OUTPUT	750 to 4500 lumens
OPERATING TIME	2 to 12 hours
BATTERY SPECIFICATION	Li-Ion 14.8V, 5200 mAh, 76.96Wh
DIMENSION	11-3/16 × 7 × 5-1/8 Inch (288 × 176 × 131 mm)
WEIGHT	2.180 kg



180° Horizontal



90° Vertical




Duo Play



Water & Dust Proof



Power Bank in Battery



Impact Resistant

SAFETY INFORMATION

- Follow workshop health & safety rules, regulations and conditions when using the rechargeable floodlight.
- When not in use, rechargeable floodlight should be stored in a dry location to inhibit rust.
- During their period of use, accessories must be checked for wear, cracks and other damage, replace any damaged or worn parts.
- Use genuine parts only. Unauthorized parts may be dangerous and will void the warranty.
- Keep the rechargeable floodlight clean and in good working order for best and safest performance.
- DO NOT use the rechargeable floodlight in the immediate vicinity of inflammable materials or gases.
- DO NOT point the rechargeable floodlight directly in your own or any other person's or animal's eyes.
- DO NOT drop, throw or abuse the rechargeable floodlight.
- Eyes protection: Wear a protective mask or protective eyewear.
- Check that the product has not suffered any damage during transport or storage. Clean and remove any dust or residual packing material.
- Read the instructions carefully before using rechargeable floodlight and keep them for further reference.

WARNING!

- DO NOT immerse rechargeable floodlight in water.
- DO NOT place rechargeable floodlight near a fire or any other source of intense heat.
- DO NOT attempt to open, disassemble, modify or service the rechargeable floodlight.
- DO NOT expose rechargeable floodlight to temperatures above 40 °C (104 °F).
- DO NOT use rechargeable floodlight if you suspect that the batteries or the casing is damaged.

TROUBLESHOOTING

PROBLEM	POSSIBLE CAUSE	CORRECTIVE ACTION
The floodlight has low lumen output or does not work	Low battery	Recharge the battery
If the floodlight still doesn't work		Contact nearest authorized service dealer

DISPOSAL

The components or the used products must be given to companies that specialize in the disposal and recycling of industrial waste.

PACKAGE CONTENT

DESCRIPTION	QTY.
Duo-Play Super Power Rechargeable Floodlight	1
Charger	1
O.I.P.M.	1

OPERATING INSTALLATION

1. Fully charge the battery before the first use. To charge, remove the battery from the light by tilting the light and sliding the battery out while pressing the button on the battery.
2. Now connect the battery to the power source with the help of charger provided with it.
3. While charging, the green LED charge indicators at the top of the battery, near the power button, will blink continuously.
4. When the battery is fully charged, all the indicator LEDs will turn green. Full charging takes about 4-5 hours.
5. Slide back the battery into the light again till a click sound is heard.
6. Press the power button located at the top of the light
 - Once for 750 lumens (25% intensity)
 - Twice for 1500 lumens (50% intensity)
 - Three times for 3000 lumens (75% intensity)
 - Four times for 4500 lumens (100% intensity)
 - Five times for switching "OFF" the light.
7. *To mount the floodlight on the tripod remove the screw from the top of the tripod. Place the floodlight on the tripod and align the centre hole of the base of the floodlight to the hole on the top of the tripod. Now secure the assembly using the screw.

MAINTENANCE

- Always use the charger provided with the floodlight for charging.
- Clean any dirt from the housing or the lens immediately, since it could cause overheating.
- If required, clean with a dry or slightly moist, clean cloth and a mild detergent. Do not use cleaners that contain abrasives or solvents.
- Fully charge the floodlight before storing it for a long time.
- When not in use, floodlight should be stored in a dry location.

