

## WL9K - WHEEL LOCK REMOVAL KIT



Item: WL9K

Description: WHEEL LOCK REMOVAL KIT

**Notes:** WL9K8: Large diameter Chrysler lock  
WL9K4: GM spline hubcap locks: Find the best-fit position and slip or tap tool onto splined hubcap lock. Turn tool with a 3/4" wrench the remove lock. Do not use an impact wrench with this tool.  
WL9K3: Ford and Chrysler hubcap locks: Drive tool onto lock. Turn tool with a 3/4" socket to remove lock. Large GM triangular well hubcap locks: Insert hex end of tool into well. Turn with a 3/4" wrench to remove lock.  
WL9K5: Stripped 18mm lug nuts, GM wheel cover locks, 88-89 Ford wheel locks: Drive socket onto lock. Turn tool with a 1/2" drive to remove lock.  
WL9K2: Standard wheel locks, large GM wheel cover locks: Drive socket onto lock. Turn tool with a 1/2" drive to remove lock.  
WL9K1: GM hubcap locks: Drive tool onto lock. Turn tool with a 3/4" socket to remove lock.  
WL9K7: Oversize wheel locks: Drive socket onto lock. Turn tool with a 1/2" drive to remove lock.  
WL9K6: Corvette, GM "N" and "F" body wheel locks (Grand Am, Firebird, Bonneville, Olds Calais, Buick Regal): Drive socket into lock. Turn tool with a 1/2" drive tool to remove lock.

Figure No	Part Number	Description	No. Reqd	Warranty Code
1	WL9K1	GM HUBCAP LOCK REMOVER	1	A
2	WL9K2	MCGARD WHEEL RELEASES & GM	1	A
3	WL9K3	FORD & CHRYSLER HBCAP REMOVER	1	A
4	WL9K4	GM SPLINE HUBCAP LOCKS	1	A
5	WL9K5	FORD WHEEL LOCKS & GM REMOVER	1	A
6	WL9K6	CORVETTE BODY WHEEL LOCKS	1	A
7	WL9K7	MCGARD WHEEL COVER LCK REMOVER	1	A
8	WL9K8	CHRYSLER HUBCAP LOCKS	1	A
9	WL9K9	LUGNUT REMOVER PUNCH	1	A